



EC 90

Electrolyte Analyser



Making Automation Affordable
for Labs Everywhere

www.erbamannheim.com

EC 90

Thanks to its biosensor innovative technology, high quality components and simplified daily routine, this next generation electrolyte analyser increases productivity, turnaround time and results accuracy.

Measuring Na^+ , K^+ , Cl^- and iCa^{2+} , the EC 90 ISE analyser takes laboratory measurements to new heights. By utilizing the innovative solid ISE cutting edge technology, the EC 90 is designed to be easy to use, efficient in operation and reliable.

The Magic is in the BIOSensor

PATENTED TECHNOLOGY



INNOVATIVE

- Clean biosensor technology
- Maintenance free technology
- Advanced connectivity and data management
- 35 μL Sample Volume
- Low reagent consumption
- 35 seconds analysis time




PRECISE

- Integrated reference sensor
- Automatic 1 and 2-point calibrations
- Fully functional QC module
- Within-run precision $< 1\%$ CV
- Extended linearity of all parameters
- Advanced flagging



ACCESSIBLE

- Large touch screen and clean software design
- 3 months cartridge life
- Self-contained waste
- Plug and play
- 4 sizes of cartridge: x small, small, medium, large



THE CARTRIDGES



ADAPTIVE

Broad range of sizes for your workload – all cartridges store waste for easy handling and simple disposal.



SUSTAINABLE

The EC90 cartridge won a Sustainability Design Award in Germany and Austria for innovative packaging construction, which helps reduce the environmental impact of disposable elements.



CAT NO	PRODUCT NAME	PACK SIZE
INS00079	EC 90	Analyser with accessories
REG00065	EC cartridge XS	250 samples / 2 months
REG00058	EC cartridge S	500 samples / 3 months
REG00056	EC cartridge M	1000 samples / 3 months
REG00057	EC cartridge L	3000 samples / 3 months
REG00066	EC cartridge XS plus iCa	250 samples / 2 months
REG00061	EC cartridge S plus iCa	500 samples / 3 months
REG00062	EC cartridge M plus iCa	1000 samples / 3 months
REG00063	EC cartridge L plus iCa	3000 samples / 3 months
REG00059	EC urine diluent	100 mL
REG00064	EC BioSensor	1 unit

TECHNICAL SPECIFICATIONS

Touch Screen	Operating Conditions
8.4 inch colour touch screen	15–35 °C (59–95 °F) / 15–90 % humidity
Display	Electronics
600 × 800 pixel graphic display	microprocessor controlled
Power	Connectivity
100–240 VAC 50/60 Hz 60 W	2 × USB-A, 1 × USB-B, 1 × LAN, 1 × RS232
Dimension	Weight
D: 425 mm × W: 268 mm × H: 334 mm	< 8 kg
Auto Sampler	Printout
to be announced	built-in, 24 column thermal printer
Barcode Scanner	
Sample/Patient ID, QC Materials Data	

Metrological data	Resolution	Display Range	Reproducibility (% CV)		
			Within-Run	Between-Runs	Measuring range [mmol/L]
Serum, plasma, aqueous, whole blood	[mmol/L]	[mmol/L]			
Na ⁺	0.1	20–200	≤ 1 % CV	≤ 2 % CV	100–200
K ⁺	0.01	0.2–40	≤ 1 % CV	≤ 2.5 % CV	1–15
Cl ⁻	0.1	25–200	≤ 1 % CV	≤ 2.5 % CV	50–170
iCa ²⁺	0.01	0.1–6.0	≤ 0.02 SD in mmol/L	≤ 0.03 SD in mmol/L	0.1–2.5
Urine (diluted 1:3)					
Na ⁺	0.1	13–400	≤ 5 % CV	≤ 5 % CV	25–400
K ⁺	0.01	2.4–180	≤ 5 % CV	≤ 5 % CV	10–180
Cl ⁻	0.1	25–500	≤ 5 % CV	≤ 5 % CV	40–400

Erba Lachema s.r.o. reserves the right to modify, alter, add and delete any of the specifications, applications and terms and conditions outlined in the brochure and shall be under no obligation to notify the user of the amendments. The information on this brochure is presented as general information and no representation or warranty. The product is not currently cleared for sale in the USA. 2021, Erba Lachema s.r.o., Czech Republic, all rights reserved.

Parameters	Technology
Na ⁺ , K ⁺ , iCa ²⁺ , Cl ⁻	electrochemistry, thick film biosensor cartridge
Principle	Sample Type
direct measurement	whole blood, plasma, serum, dil. urine, aqueous sol.
Sample Volume	Sample Temperature
35 and 90 µL measuring modes	15–35 °C
Throughput	Analysis Time
90 samples/hour	35 sec
Data Storage	Data Management
10 000 samples	fully functional QC with Levey-Jennings and Westgard rules, programmable reference ranges, advanced flagging
Language/s	1-point calibration
EN, PT, FR, DE, ES, RU, PL	automatic 1-point calibration with every sample or on-demand
2-point calibration	Standby Mode
automatic 2-point calibration every 12 hours or on demand	automatically controlled or user defined



Scan the QR code to play the video

Erba Lachema s.r.o.

Karásek 2219/1d, 621 00 Brno,

Czech Republic

www.erbamannheim.com



TOTAL SOLUTIONS FOR CLINICAL DIAGNOSTICS
Version No 1.2_23.09.2024

